



Specification Statements FSH Products

1. Electric Drop Bolt DB1260 PTL - Power to Lock

"The power to lock (PTL) flush mount drop bolt must be equal in all respects to FSH model DB1260PTL. The device must be provided with a 1 year warranty and fire tested up to a 4 hour fire resistance rating to both Australian and British Fire Test Standards (if fitted with alternative items of hardware). It has to have a holding strength of up to 300kg, provide internal control circuits to prevent damage and false operation and contain an in-built time delay switch."

Product features

- Internal control circuits to protect drop bolt pin from damage
- Auto lock function
- Built-in varistor (MOV) for surge protection
- Time delay setting at 0/3/6/10 seconds
- Low power consumption
- Anodised Aluminium body case
- 1 year warranty
- Power to lock (PTL)
- Fire tested 4 hours (DB1260)

2. Electric Drop Bolt DB1260 PTR - Power to Release

"The power to release (PTR) flush mount drop bolt must be equal in all respects to FSH model DB1260PTR. The device must be provided with a 1 year warranty and fire tested up to a 4 hour fire resistance rating to both Australian and British Fire Test Standards (if fitted with alternative items of hardware). It has to have a holding strength of up to 300kg, provide internal control circuits to prevent damage and false operation and contain an in-built time delay switch."

Product features

- Internal control circuits to protect drop bolt pin from damage
- Auto lock function
- Built-in varistor (MOV) for surge protection
- Time delay setting at 0/3/6/10 secs
- Low power consumption
- Anodised Aluminium body case
- 1 year warranty
- Power to release (PTR)
- Fire tested 4 hours (DB1260)