

The Euclid Chemical Company 19218 Redwood Road Cleveland, OH 44110

Phone: 800-321-7628 Fax: 216-531-9596 www.euclidchemical.com

Maintenance of a Diamond Hard Treated Floor

♦ Post Fixturing:

Clean the floor thoroughly. Using a high-speed, propane burnisher, equipped with a diamond impregnated pad, polish the floor to a high gloss finish. Applying additional Diamond Hard during this process might be required to achieve desired level of gloss.

♦ First Six Months:

Clean the floor often during the first several months after application of Diamond Hard, and wash on a regular basis thereafter. The more buffing the Diamond Hard receives, the greater the sheen of the floor.

♦ Detergents / Strippers:

Use mild (neutral to high pH) soaps or detergents to clean your Diamond Hard treated floor. Do not use acidic cleaners or detergents. Spot clean to remove grease, oil, or tire marks with EUCO Clean & Strip.

♦ Protection:

Protect the floor from spills as much as possible. The sealing and densifying action of Diamond Hard will increase over the first year of service, but good housekeeping practices and quick clean-up of spills are always recommended to keep the floor looking good. The longer a spill remains on the floor, the more likely it is to stain.

Maintenance:

The frequency of routine maintenance should be scheduled based on the type and amount of traffic, as well as exposure to abrasive chemicals and/or materials. The use of a walk-behind or ride-on floor scrubber to clean and buff a Diamond Hard treated floor will produce the best results, and is most practical on large floors.

♦Waxes / Coatings

Waxes or other coatings applied over a Diamond Hard treated floor are not recommended.

An RPIT Company ISO 9001 Certified UL File #A3129