



# MATERIAL SAFETY DATA SHEET

## Sikaflex® 11FC (All colors)

### HMIS

HEALTH	*2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	C

### 1. Product And Company Identification

<b>Supplier</b> Sika Corporation 201 Polito Ave Lyndhurst, NJ 07071  <b>Company Contact:</b> EHS Department <b>Telephone Number:</b> 201-933-8800 <b>FAX Number:</b> 201-933-9379 <b>Web Site:</b> www.sikausa.com	<b>Manufacturer</b> Sika Corporation 201 Polito Ave Lyndhurst, NJ 07071  <b>Company Contact:</b> EHS Department <b>Telephone Number:</b> 201-933-8800 <b>FAX Number:</b> 201-933-9379 <b>Web Site:</b> www.sikausa.com
<b>Supplier Emergency Contacts &amp; Phone Number</b> CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887	<b>Manufacturer Emergency Contacts &amp; Phone Number</b> CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887

**Issue Date:** 08/23/2007  
**Product Name:** Sikaflex® 11FC (All colors)  
**CAS Number:** Not Established  
**Chemical Family:** Polyurethane  
**MSDS Number:** 4172  
**Product Code:** 0481522

### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number		Percent Of Total Weight
POLYISOCYANATE PREPOLYMER	Trade Secret		
XYLENE (MIXED ISOMERS)	1330-20-7	<	4

### 3. Hazards Identification

**Eye Hazards**  
 May cause eye irritation.

**Skin Hazards**  
 May cause skin irritation. Prolonged and/or repeated skin contact may cause an allergic reaction/sensitization.

**Ingestion Hazards**  
 May be harmful if swallowed.

**Inhalation Hazards**  
 May cause nose, throat, and lung irritation. May cause an allergic respiratory reaction / sensitization after prolonged or repeated contact. Reports have associated repeated and prolonged exposure to some of the

# MATERIAL SAFETY DATA SHEET

## Sikaflex® 11FC (All colors)

### 3. Hazards Identification - Continued

#### Inhalation Hazards - Continued

chemicals in this product with permanent brain, liver, kidney, and Central Nervous System damage. Headaches and dizziness may result.

### 4. First Aid Measures

#### Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

#### Skin

In case of contact, immediately flush skin with soap and plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

#### Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel. If victim is fully conscious, give one or two cups of water or milk to drink. Seek medical attention immediately.

#### Inhalation

Remove to fresh air. If not breathing, give artificial respiration.

### 5. Fire Fighting Measures

**Flash Point:** N/A °F

**Flash Point Method:** Solid per ASTM D4359

**Autoignition Point:** N/AV °F

**Lower Explosive Limit:** N/AV

**Upper Explosive Limit:** N/AV

#### Fire And Explosion Hazards

During a fire, irritating and/or toxic gases and aerosols from the decomposition/combustion products may be present.

#### Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO<sub>2</sub>.

#### Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

### 6. Accidental Release Measures

Avoid release to the environment. Use appropriate Personal Protective Equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Do not flush to sewer or allow to enter waterways. Ventilate enclosed area.

### 7. Handling And Storage

#### Handling And Storage Precautions

Keep out of reach of children. Not for internal consumption.

#### Handling Precautions

Condition to 65 - 85F before using. If closed container is exposed to heat, pressure can build up. If moisture enters container, pressure may build up due to reaction.

#### Storage Precautions

Store at 40 - 95F. Store in cool dry area in tightly closed containers, away from sparks and open flames.

# MATERIAL SAFETY DATA SHEET

## Sikaflex® 11FC (All colors)

### 7. Handling And Storage - Continued

#### Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

### 8. Exposure Controls/Personal Protection

#### Engineering Controls

Use of a system of local and/or general exhaust is recommended to keep employee below applicable exposure limits. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

#### Eye/Face Protection

Safety glasses with side shields or goggles.

#### Skin Protection

Chemical-resistant gloves. Lab coat or other work clothing to prevent skin exposure (Long sleeve shirt and long pants). Launder before reuse.

#### Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

#### Other/General Protection

Wash thoroughly after handling.

#### Ingredient(s) - Exposure Limits

POLYISOCYANATE PREPOLYMER

ACGIH TLV: NOT ESTABLISHED

OSHA PEL: NOT ESTABLISHED

IARC: NO

NTP: NO

XYLENE (MIXED ISOMERS)

ACGIH TLV-STEL 150 ppm

ACGIH TLV-TWA 100 ppm

OSHA PEL-TWA 100 ppm

### 9. Physical And Chemical Properties

#### Appearance

Paste (solid)

#### Odor

Aromatic Odor

**Chemical Type:** Mixture

**Physical State:** Solid

**Melting Point:** N/AV °F

**Boiling Point:** N/AV °F

**Specific Gravity:** 1.27

**Percent VOCs:** 3.8

**Packing Density:** 10.6 pounds/gallon

**Vapor Pressure:** N/AV

**Vapor Density:** > AIR

**Solubility:** N/AV

**Evaporation Rate:** Slower than ether

# MATERIAL SAFETY DATA SHEET

## Sikaflex® 11FC (All colors)

### 9. Physical And Chemical Properties - Continued

#### Odor - Continued

VOC Content: < 50 grams/liter

### 10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

#### Conditions To Avoid (Stability)

Open Flame, Heat

#### Incompatible Materials

Water, Alcohols and Amines

#### Hazardous Decomposition Products

CO, CO<sub>2</sub>, NO<sub>x</sub>, Smoke, Fumes

### 11. Toxicological Information

No Data Available...

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

### 14. Transport Information

#### Proper Shipping Name

Not regulated by the USDOT.

### 15. Regulatory Information

#### U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

#### SARA Hazard Classes

Acute Health Hazard

Chronic Health Hazard

#### SARA Title III - Section 313 Supplier Notification

This product contains the following toxic chemicals that are subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372.

XYLENE (MIXED ISOMERS) (1330-20-7) <4 %

This information must be included on all MSDSs that are copied and distributed for this material.

#### Ingredient(s) - U.S. Regulatory Information

XYLENE (MIXED ISOMERS)

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

SARA - Acute Health Hazard

# MATERIAL SAFETY DATA SHEET

## Sikaflex® 11FC (All colors)

### 15. Regulatory Information - Continued

#### Ingredient(s) - U.S. Regulatory Information - Continued

SARA - Chronic Health Hazard

SARA - Fire Hazard

#### Ingredient(s) - State Regulations

XYLENE (MIXED ISOMERS)

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

New Jersey - Special Hazard

Pennsylvania - Workplace Hazard

Pennsylvania - Environmental Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

### 16. Other Information

#### HMIS Rating

Health: \*2

Fire: 1

Reactivity: 0

PPE: C

#### Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201 933 - 8800

This MSDS Supersedes A Previous MSDS Dated: 08/02/2005

### Disclaimer

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikacorp.com](http://www.sikacorp.com) or 201-933-8800.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000