

WATERPROOFING

Sure-Seal® Termination Bar

Description

The Sure-Seal Termination Bar is an extruded aluminum bar designed for securing and sealing flashing terminations in accordance with current Carlisle Specifications.

Features and Benefits

- Corrosion resistant 6063-T6 extruded aluminum
- Pre-Punched 6" (150 mm) o.c. and 1" (25 mm) from each end
- Sealant ledge to hold the Lap Sealant and provide stability
- Serrated back provides increased surface area contact with membrane to compress the Water Cut-Off Mastic

Installation

1. Peel back flashing material approximately 1" (25 mm).
2. Apply Water Cut-Off Mastic between substrate and flashing (approximately 10' (3 m) per tube).
3. Install termination bar by fastening 12" (300 mm) o.c. maximum with a fastener compatible with the substrate to achieve constant compression of Water Cut-Off Mastic. Start fastening at one end of the bar and proceed to the next slot (12" max.) to eliminate bowing caused by improper installation.
4. Trim top edge of flashing flush with top of termination bar.
5. Apply Lap Sealant to top edge of bar and feather.

Limitations

Apply on a hard, smooth surface only; not for use on wood.

Water Cut-Off Mastic must be held under constant compression. Do not wrap compression termination around corners.

When field cutting is necessary, remove any burrs or sharp edges from the bar.

Allow ¼" (6 mm) minimum to ½" (12 mm) maximum spacing between bars.

Typical Properties

| Property | Results |
|------------|-----------------------------------|
| Material | 6036-T6 Extruded Aluminum |
| Dimensions | 1" (25 mm) wide x 10' (3 m) long |
| Packaging | 50 pcs; 500 lf (152 m) per carton |
| Weight | 69 lbs. (31 kg) carton |

Limited Warranty

Carlisle Coatings & Waterproofing Incorporated (Carlisle) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Carlisle materials prove to contain manufacturing defects that substantially affect their performance, Carlisle will, at its option, replace the materials or refund its purchase price. This limited warranty is the only warranty extended by Carlisle with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Carlisle specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever. The dollar value of Carlisle's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Carlisle material in question.