



# Tremco Sealants - Basic Uses and Classifications

Description	ASTM C920	TYPE: Single/Multi-Component	GRADE: Pourable or Non-Sag	CLASS: Cyclic Movement +/-	USE: NT, M, A, O	USE: T, I, G	ASTM C834	ASTM C1248	ASTM C1382	ASTM E84	Federal Spec TT-S-001543A	Federal Spec TT-S-00230C	Federal Spec TT-S-00227E	TYPE I Self-Leveling	TYPE II Non-Sag	CLASS A 50%max, B 25%max	MCG-1-25-B-N	MCG-2-40-B-N	CAN/CGSD-19.13-M87	CAN/CGSD 19GP17M	CAN/CGSD 19-24-M90	AAMA VCL Listed	COLA Approval, City of LA	ULC Registered	EIMA Test 300.01	USDA	CFIA Approved	SWRI Validated Product	GREENGUARD Children & Schools	
<b>Vulkem 116</b> ▲ Polyurethane, for vertical/horizontal & traffic /non-traffic	●	S	NS	25	●	T,I					●		●	A				●				●								
<b>Vulkem 45SSL</b> ◆ Polyurethane, semi-self-leveling (up to 6% slope)	●	S	P	35	M,A,O	T,I					●	●				●		●												
<b>Dymonic 100</b> Polyurethane with high performance & high movement	●	S	NS	50	●	T,I			●		●		●	A				●											●	
<b>Dymonic FC</b> Polyurethane Hybrid, for vertical & non-traffic horizontal	●	S	NS	35	●		●				●		●	A				●		●					●	●			●	
<b>Dymonic</b> Polyurethane, for vertical & non-traffic horizontal	●	S	NS	35	●						●		●	A				●				●				●	●		●	
<b>Dymeric 240*</b> Epoxidized Polyurethane, vertical/horizontal & traffic/non-traffic	●	M	NS	50	●	T					●		●	A						●						●	●	●	●	
<b>Dymeric 240FC</b> Epoxidized Polyurethane fast cure, vertical /horizontal & traffic/non-traffic	●	M	NS	50	●	T,I					●		●	A						●						●	●	●	●	
<b>THC 900</b> Polyurethane, self-leveling for traffic & non-traffic areas	●	M	P	25	M,O	T					●	●		A												●	●			
<b>THC 901</b> Polyurethane, semi-self-leveling (up to 10% slope)	●	M	P	25	M,O	T					●	●		A												●	●			
<b>Spectrem 1</b> Silicone neutral cure, low modulus for vertical	●	S	NS	100/50	●	G	●	●	●	●	●		●	A		●	●						●	●	●	●	●	●	●	
<b>Spectrem 2</b> Silicone neutral cure, for vertical, structural glazing	●	S	NS	50	●	G	●			●	●		●	A				●			●				●	●	●	●	●	
<b>Spectrem 3</b> Silicone neutral cure, low modulus for vertical	●	S	NS	50	●	G	●	●		●	●		●	A				●					●	●					●	
<b>Spectrem 4-TS</b> Silicone neutral cure, low modulus for vertical	●	M	NS	50	●	G	●	●		●	●		●	A				●					●	●					●	
<b>Spectrem 800</b> Silicone neutral cure, low modulus, vertical/horizontal & highway	●	S	NS	100/50	M,A,O	T				●	●		●	A				●												
<b>Spectrem 900SL</b> Silicone neutral cure, low modulus for horizontal & highway	●	S	P	100/50	M,A,O	T				●	●	●		A				●												
<b>Simple Seal</b> Silicone, preformed low modulus tape for bridge joints																													●	
<b>Tremsil 200</b> Silicone acetoxy cure, for vertical	●	S	NS	25	NT,A,O	G				●	●		●	A				●								●			●	
<b>Tremsil 600</b> Silicone neutral cure, for vertical	●	S	NS	25	NT,A,O	G				●	●		●	A				●			●				●	●			●	
<b>Proglaze SSG</b> Silicone, neutral cure, high modulus, fast cure, structural	●	S	NS	25	NT,A,O	G				●	●		●	A				●		●					●				●	
<b>Proglaze II</b> Silicone, high modulus, 2-part structural glazing	●	M	NS	25	NT,A	G					●	●	●	A											●				●	
<b>Proglaze</b> Silicone acetoxy cure, for vertical	●	S	NS	25	NT,A,O	G				●	●		●	A											●				●	
<b>MONO 555</b> Acrylic Terpolymer, glazing/flaming sealant		S	NS	12.5							●		●																	
<b>Tremflex 834</b> Acrylic Latex, ideal for interior applications		S	NS	12.5			●		●											●										●
<b>Butyl Sealant</b> Butyl, curtainwall, bedding joints, secondary glazing seals		S	NS	10																										
<b>Curtainwall Sealant</b> Butyl, non-curing/non-skinning for bedding joints		S	NS																											
<b>Acoustical Sealant</b> Butyl, non-curing/non-skinning, sound dampering sealant		S	NS																											
<b>Tremco 830</b> Thermoplastic, exterior grade, non-structural glazing/sliding		S	NS	12.5									●																	
<b>illmod 600</b> Polyurethane, preformed, pre-compressed, impregnated foam tape			NS						●																					●

▲ These materials are also available with quick-cure catalyst. ◆ These materials can be water catalyzed. Please contact Technical Services for more info. \* Product not for use in the United States.