

TR¹

HEA TIP




HEA | HIGH EFFICIENCY AIRLESS™

REVOLUTIONARY LOW PRESSURE TECHNOLOGY

- Optimized to spray all architectural paints and coatings at 1,000 psi at production speed
- Decreases overspray up to 55% allowing contractors to spray more
- Less pressure equals less stress extending pump life and extending time between repacks
- Two times the life of a standard reversible tip
- Patented design

HIGHLY EFFICIENT FAN PATTERN



Latex paint through a standard 517 tip at 1,000 PSI



Latex paint through a HEA 517 tip at 1,000 PSI

- Feathered edge provides consistent coverage
- More forgiving pattern that decreases runs and drips
- Less kickback when triggered providing more control and less overspray
- Fits all industry standard guards

MAXIMIZE THE PERFORMANCE OF YOUR HEA TIP



HEA Pressure Gauge Part No. 0580495



THE RIGHT MIX FOR PRODUCTION 330-XXX

	INCHES (MM)	0.011	0.013	0.015	0.017	0.019
FAN WIDTH	4-6 (102-152)	211	213			
	6-8 (152-203)	311	313			
	8-10 (203-254)	411	413	415	417	
	10-12 (254-305)			515	517	519
	12-14 (305-356)			615	617	619
	FLOW RATE (GPM/LPM)	0.09/0.34	0.12/0.45	0.18/0.68	0.24/0.91	0.31/1.17