

Capital Tape Co, Inc
4920 Commerce Parkway #11
Cleveland, OH 44128
Fax: 216.292.3435



V1526 Series – Medium Density PVC Foam W/ Plastic Liner

Aggressive, pressure sensitive adhesive on both sides of a medium density closed cell PVC foam. These tapes provide an excellent combination of light density flexibility with heavy density strength. Products feature an easy release film liner. Tested and approved to AAMA 810.1-92 expanded cellular glazing tapes; these foams are silicone compatible.

- Excellent in glazing applications
- Maintains a seal in high movement joints
- Effectively functions as a thermal break and insulator
- Excellent resistance to fungi, oxidation, and weather

Physical properties:

Density	ASTM D-1667	15 lbs./cu.ft.
Hardness (Shore 00)	ASTM D-2240	40
Force to Compress (@ 25%)	ASTM D-1667	7 psi 48 kPa
Compression Set 25% (% loss from original height)	ASTM D-1667	8%
Water absorption (% by volume)	GTP	1.0
Tensile strength	ASTM D-412	80 psi 550 kPa
Percent elongation	ASTM D-412	160
Thermal conductivity (K factor) (btu-in.)/(hr.sq.ft.) (F°)	ASTM C-518	0.30
Recommended Service Temperature:		-30°F to 200° F -35°C to 90° C
Recommended Application Temperature:		50° F to 110° F 10° C to 45° C
Fire Rating		Meets or exceeds FMVSS 302A Self-Extinguishing/No Burn Rate

These are approximate values and do not constitute a warranty. It is the customer's responsibility to determine these products fitness for use in the intended end use application. Test data contained herein is believed to be reliable and it is not stated as, or to be taken as, a specification for these products.